

	4	5
--	---	---



Normal

PS: 1. The wave distance dimension is regarded as the reference size and is not included as an inspection item.

2. If the customer specifies the wall thickness, the inner diameter size will not be controlled.

	4	5
--	---	---

6		7		8	
Date		Details			
2021/03/18		The inner diameter of M48 has been changed from 478 ± 0.5 to 48.5 ± 0.5. AD to A1			
2021/06/25		New mold number added, product specifications expanded; A1 to A2			

NOTE:

- 1.MATERIAL: Polyamide 12 (PA12)
- 2.TEMPERATURE: -40℃~105℃
- 3.THERMAL: 150℃/240H
- 4.FLAME RETARDANT RATING: UL94 HB
FMVSS 302:<100mm/min
- 5.COLOUR:TBD
- 6.STANDARD: UL94 V-0



吴江市拓研电子材料有限公司
拓研配线

设计 SIGN		日期 DATE	版本号 REV.NO.	单位 UNIT	比例 SCALE	吴江市拓研电子材料有限公司 拓研配线
审核 PROVE		2021-06-25	A2	mm		Product: PA Corrugated Conduit
批准 HORIZE		共1页 TOTAL SHEETS	第1页 NO. OF SHEETS		投影符号:	Model: PABHB

6

7

8