

1				2				3			
A	Quality standards										
	M	20-100	01-200	201-300	301-500	501-1000	>1000				
	4.5 bis/to 7.5	±5	±5	±6	±7	±8	±15				
	8 bis/t 13	±5	±6	±7	±8	±9	±15				
	14 bis/to 17	±5	±6	±8	±9	±10	±15				
	18 bis/to z3	±6	±7	±9	±10	±10	±13				
	25 bis/to 48	±7	±7	±9	±10	±10	±1%				
B	Normal										
	No	mold	Specification	ID A	OD B	Thicknes T	C	D	Bending Radius		
	1	TY-WJ-B001	4.5*7	5.0±0.3	7.3±0.3	0.25±0.05	2.1	1.5	≥8		
	2	TY-MJ-8B003	5*7(真空)	5.0±0.3	7.1±0.3	0.25±0.05	2.1	1.4	≥B		
	3	TY-MJ-B004	5.2*7.4	5.4±0.3	7.4±0.3	0.25±0.05	2.2	1.5	≥8		
	4	TY-MJ-B005	5.5*8(圆)	5.5±0.3	8.0±0.3(圆)	0.25±0.08	2.0	1.4	≥16		
	5	TY-WJ-B006	5.5*8(方)	5.5±0.3	8.0±0.3(方)	0.25±0.08	2.0	1.4	≥16		
	6	TY-MJ-8007	6.5*10	6.5±0.3	10.0±0.3	0.25±0.08	2.8	2.0	≥13		
	7	TY-J-B008	6.7*10	6.7±0.3	10.0±0.3	0.25±0.08	2.8	2.0	≥13		
	8	TY-WJ-8009	7.5*10.4	7.5±0.4	10.4±0.4	0.25±0.08	2.8	1.9	≥15		
	9	TY-J-B010	7.3*10.7	7.3±0.4	10.7±0.4	0.25±0.08	2.7	2.1	≥15		
	10	Y-MJ-B011	7.5*10.2	7.5±0.4	10.2±0.4	0.25±0.08	2.8	1.9	≥15		
	11	TY-MJ-B012	7.4*10.3(真空)	7.4±0.4	10.2±0.4	0.25±0.08	2.5	1.8	≥15		
	12	TY-WJ-B013	8*11.6	8.2±0.4	11.6±0.4	0.25±0.08	2.8	1.9	≥15		
	13	TY-MJ-B016	17*21.2(细)	17.1±0.4	21.2±0.4	0.35±0.10	3.3	2.3	≥45		
	14	TY-J-B019	6.89.8(JE)	6.9±0.4	9.9±0.4	0.25±0.08	2.6	1.7	≥16		
	15	TY-J-B022	16.6*21.2(S)	16.6±0.4	21.2±0.4	0.35±0.10	3.3	2.3	≥45		
	16		21.3*25.4(S)	21.3±0.4	25.4±0.4	0.40±0.10	3.1	2.2	≥50		
	17	TY-J-B023	12.7*15.8(S)	12.7±0.3	15.8±0.3	0.30±0.08	2.6	1.8	≥30		
	18		25.8*31.2(S)	25.8±0.4	31.2±0.4	0.40±0.10	3.3	2.3	≥60		
	19	TY-WJ-B024	29*34.5	29±0.5	34.5±0.5	0.40±0.10	5.1	3.1	≥65		
	20	TY-MJ-B025	36*42.5	36±0.5	42.5±0.5	0.45±0.10	5.1	3.3	≥90		
	21	TY-WJ-B026	14.3*18.5	4.3±0.5	18.5±0.5	0.30±0.08	4.0	2.5	≥40		
	22		17*21.2(1#)	7.0±0.5	21.2±0.5	0.35±0.10	4.0	2.7	≥45		
	23	TY-UJ-B027	10*13(1#)	0.0±0.5	3.0±0.5	0.30±0.08	2.8	1.9	≥20		
	24		1721.2(2#)	17.0±0.5	21.2±0.5	0.35±0.10	4.0	2.7	≥45		
	25	TY-WJ-B028	1*15	11.0±0.5	15.0±0.5	0.30±0.08	2.8	1.8	≥25		
	26		25*30	25.4±0.5	30.5±0.5	0.40±0.10	4.3	2.7	≥60		
	27	TY-WJ-B029	11*14	1.0±0.5	14.0±0.5	0.30±0.08	2.8	1.9	≥20		
	28		23*28.5(低波)	23.0±0.5	28.5±0.5	0.40±0.10	4.7	3.0	≥55		
	29	TY-WJ-B030	16*20	16.4±0.5	20.5±0.5	0.35±0.10	3.5	2.3	≥45		
	30		8*22	18.3±0.5	22.5±0.5	0.35±0.10	3.7	2.5	≥50		
	31	TY-J-B031	10*13(2#)	0.0±0.5	13.0±0.5	0.30±0.08	2.8	1.9	≥20		
	32		23*28.5	23.0±0.5	28.5±0.5	0.40±0.10	4.7	3.0	≥55		
	33	TY-WJ-B032	12*15.8(1#)	2.0±0.5	15.8±0.5	0.30±0.08	3.1	2.0	≥30		
	34		20*25(1#)	20.4±0.5	25.0±0.5	0.40±0.10	4.7	3.0	≥50		
	35	TY-J-8033	3*17	13.7±0.5	17.0±0.5	0.30±0.08	3.5	2.5	≥35		
	36		9*23	9.4±0.5	23.3±0.5	0.35±0.10	3.7	2.6	≥50		
	37	TY-WJ-B034	12*15.8(2#)	12.0±0.5	15.8±0.5	0.30±0.08	3.1	2.0	≥30		
	38		20*25(2H)	20.4±0.5	25.0±0.5	0.40±0.10	4.7	3.0	≥50		
	39	TY-J-B035	12*15.8(低波)	2.0±0.5	15.8±0.5	0.30±0.08	3.1	2.1	≥3		
	40		25*30(低波)	25.4±0.5	30.5±0.5	0.40±0.10	3.7	2.2	≥60		
	41	TY-WJ-B036	42*50	42.0±0.5	50.0±0.5	0.45±0.10	6.2	3.7	≥100		
	42	TY-WJ-B037	48*54.5	48.5±0.5	54.5±0.5	0.45±0.10	6.2	4.2	≥100		
43	TY-MJ-B039	9*12	9.7±0.5	11.9±0.5	0.25±0.08	2.8	1.7	≥20			
44	TY-J-B040	6.6*9	6.6±0.3	9.0±0.3	0.20±0.05	2.3	1.6	≥16			
1				2				3			

4		5	